



Ledinaire panel

RC065B G5 34_36S/830_40 PSU W60L60 OC SC

Ledinaire panel, All-in, 28 W, 600x600 mm, VPC, 3400 lm, 3000 K, 4000 K, UGR19

The Philips Ledinaire panel Gen5 (RC065B/RC066B) range features a selection of popular off-the-shelf LED luminaires that offer Philips high quality at a competitive price. Reliable, energy-efficient and affordable, this latest generation of 600 x 600 mm, 620 x 620 mm, 300 x 1200 mm, and 600 x 1200 Ledinaire LED panel lights are designed for diffuse, comfortable lighting in a wide range of general lighting applications. Our range of Ledinaire panels lighting is also available with accessories for easy installation on different types of ceilings—just what you need.

Product data

General Information		Luminaire light beam spread	
Number of gear units	1 unit	Luminaire light beam spread	90°
Driver included	Yes	Unified glare rating CEN	19
Value ladder	Value	All-in Type	All-in, Multi Color Temperature
Safety device	SC [Safety cable]	Operating and Electrical	
Light Technical		Input Voltage	220 to 240 V
Luminous Flux	3,400 lm	Line Frequency	50 or 60 Hz
Luminous Efficacy (rated) (Nom)	120 lm/W	Inrush current	16 A
Correlated Color Temperature (Nom)	3000 4000 K	Inrush time	0.2 ms
Color rendering index (CRI)	80	Power Consumption	28 W
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1	Power Factor (Fraction)	0.9
Beam angle of light source	90 degree(s)	Connection	Push-in connector 2-pole
Light source color	3000K/3500K/4000K	Cable	-
Optic type	Beam angle 90°	Number of products on MCB of 16 A type B	20

Ledinaire panel

Temperature	
Ambient temperature range	-10 to +35 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit external (On/Off)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Acrylate
Fixation material	-
Housing Color	White
Optical cover finish	Microprismatic lens
Overall length	595 mm
Overall width	595 mm
Overall height	60 mm
Dimensions (Height x Width x Depth)	60 x 595 x 595 mm
Compatible ceiling or ceiling installation accessory type	Visible profile ceiling version
Approval and Application	
Ingress protection code	IP20/40 [Finger-protected;Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Photobiological risk	Photobiological risk group 0 @200mm to EN62778

Photobiological risk specification	0.2 m
EU RoHS compliant	Yes


Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.43, 0.40) SDCM ≤5(0.38, 0.38) SDCM ≤5
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance at median useful life* 50000 h	L80
Lumen maintenance at median useful life* 75000 h	-

Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product Data	
Order product name	RC065B G5 34_36S/830_40 PSU W60L60 OC SC
Full product name	RC065B G5 34_36S/830_40 PSU W60L60 OC SC
Full product code	872016951672499
Order code	911401877285
Material Nr. (12NC)	911401877285
Numerator - Quantity Per Pack	1
Net Weight (Piece)	1.650 kg
EAN/UPC - Product/Case	8720169516724
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169516953

Dimensional drawing



Ledinaire panel

