



Ledinaire All-in floodlights

BVP167 LED60/830_40_65DOB 50W SWB MDU

Ledinaire All-in floodlights, 50 W, 5500 lm, 6000 lm, 3000 K, 4000 K, 6500 K, Sensor-based dim, Symmetrical, MDU

With this Ledinaire all-in floodlights range, you can easily adjust the color temperature by a simple switch. No need to choose between warm white, neutral white or cool white anymore, you get all this in one single product ! The range comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information		Color rendering index (CRI)	
Lamp family code	LED60S [LED Module, system flux 6000 lm]	Color rendering index (CRI)	80
Number of gear units	1 unit	Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Driver included	Yes	Light source color	830 warm white and 865 cool daylight
Photocell	Photocell included	Optic type	Symmetric 110°
Light source engine type	LED system in flux	Optical cover type	Glass
Value ladder	Value	Luminaire light beam spread	110°
Embedded control	Movement detection unit	Optic type outdoor	Symmetrical
		All-in Type	All-in, Multi Color Temperature
Light Technical		Operating and Electrical	
Upward light output ratio	0	Input Voltage	220-240 V
Luminous Flux	5,500 6,000 lm	Line Frequency	50 or 60 Hz
Standard tilt angle posttop	27°	Inrush current	1.68 A
Standard tilt angle side entry	-	Inrush time	0.0082 ms
Luminous Efficacy (rated) (Nom)	110 120 lm/W	Power Consumption	50 W
Correlated Color Temperature (Nom)	3000 4000 6500 K		

Ledinaire All-in floodlights

Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug
Number of products on MCB of 16 A type B	43

Temperature

Ambient temperature range	-25 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Driver integrated on LED board (DoB)
Control interface	Sensor-based dim
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Tempered glass
Fixation material	Steel
Housing Color	RAL 7043
Mounting device	Via U Shaped Bracket, Aiming Scale Angle, Universal Installation
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	264 mm
Overall width	173 mm
Overall height	57 mm
Effective projected area	0.02775 m ²
Dimensions (Height x Width x Depth)	57 x 173 x 264 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	1.5/1.5 kV
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces

CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.440,0.403); (0.369,0.364); (0.313,0.337) SDCM<5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance at median useful life* 50000 h	80

Application Conditions


Performance ambient temperature Tq	25 °C
Suitable for random switching	Not applicable

Product Data

Order product name	BVP167 LED60/830_40_65DOB 50W SWB MDU
Full product name	BVP167 LED60/830_40_65DOB 50W SWB MDU
Full product code	872016973618499
Order code	911401894386
Material Nr. (12NC)	911401894386
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.850 kg
EAN/UPC - Product/Case	8720169736184
Numerator - Packs per outer box	16
EAN/UPC - Case	8720169736375

Ledinaire All-in floodlights

Dimensional drawing



mm	10W	20W	30W	50W	70W
A	70	82	117	150	175
B	174	191	220	255	295
C	58	58	58	58	70
D	90	109	145	185	215
E	4,2	4,2	4,5	5,5	6,5
F	4,2	4,2	4,5	6,5	6,5
G	85	97	133	173	203
H	41	50	70	90	110
I	51	60	85	110	130

